

Representative Image

Catalog No. TPL412R

Description: 125A 4CRT 1P3W 120/240V 22K IC 3R

UPC No 783164191325

Home > Load Centers > Load Centers

Main lug load centers can be used as a home's main panel or sub panel depending upon your preferences. All ABB load centers are rated up to 60 degree/75 degree centrigrade and is suitable for use with service entrance equipment when installed in accordance with electrical code. The TPL412R is made of thermoplastic and features spaces for 4, 1" breakers, a 125A main ampere rating, and an outdoor suitable enclosure.

Descriptors

Category	Load Centers
GO Schedule	RA
Grouping	Single Phase - USA

Specifications

Load Center Type	Standard
Input/Output Voltage	120/240V ac
Interrupting Capacity Rating	10
Amperage	125 A
Device type	Main Lug
Enclosure	Outdoor
Phase	1 Phase
1" Space	4
1/2" Space	8
Feed	Either
Door	Yes
GSA Compliance	Yes
Circuit Breaker Style	Plug-In
NEMA Rating	Thermoplastic
Factory Installed Ground Kit	No
Enclosure Type	Outdoor, Thermoplastic
Wires	3 Wire
Service & Voltage	1 Phase, 3 Wire, 120/240V ac

Classifications

UL/CUL Listing	UL

by ABB